



Cold in a perfect combination of Design,  
Quality and Professionalism for the Medical field.

## FREEZER 1500



### Characteristics

|   |   |
|---|---|
| Structure   | White or Stainless steel 18/10<br>int.+ext.   |
| Insulation thickness                                  | 70 (polyur. mm)   |
| Doors number  | 2   |
| Door type   | Fully Insulated   |
| Shelves nr.   | suggested 6   |
| Refrigeration type                                    | Ventilated  |
| Refrigerant type                                      | R404A   |
| Temperature range                                     | -10° -25°   |
| Temperature control/adjustment                        | ECT-F Control® : with<br>Hi/Low Temp. alarm, door<br>ajar, ON/OFF w/password                |
| Defrosting type                                       | Auto  |
| Voltage   | 230V/1/50Hz   |
| Capacity (LT)   | 1500  |
| Width (cm)  | 144   |
| Depth (cm)  | 82  |
| Height (cm)   | 210   |
| Net weight (kg)                                       | 200   |
| Equipment in accordance with                          | Directives 98/37/CE,<br>2006/95/CE, 2004/108/CE,<br>93/42/CE and following<br>modifications |
| Automatic condensate water evaporation.               |   |
| Internal cabinet with shelves/drawers interchangeable |   |

## Accessories

|   |   |
|---|---|
| Additional open wire shelf realized in sheet steel plastic coated | GSM Communicator CF2008 module                            |
| Drawer realized in aluminium                                      | Interchange Rack System for Shelves/Baskets               |
| Safety key locking  | Internal steel wire basket                                |
| Kit of castors with brakes  | Frequency 60Hz  |
| PT100 sensor  | Voltage 115V  |
| WEB LIGHT SERVER (Rete Ethernet + GSM)                            | DMLP Digital Monitor (Alarm System)®                      |
|   | Accessories for DMLP Digital Monitor® :                   |
|   | - DMLP Printer (Graphic Temp. Printer)                    |
|   | - DMLP Remote panel                                       |
|   | - Ext. terminal board for RS485/dry contacts              |
|   | -DMLP PT100 Extension module + nr.1 PT100 + 4-20mA output |

At any time, the manufacturer may bring modifications to the model above described, for technical or commercial reasons. The picture does not necessary shows the product in the standard version.



CF di Ciro Fiocchetti & C. s.n.c. via Lorenzini, 53 - 42045 Luzzara (RE) Italy -

Tel. +39 0522 976232 - Fax +39 0522 976028 - Web site: [www.fiocchetti.it](http://www.fiocchetti.it) - E-mail: [info@fiocchetti.it](mailto:info@fiocchetti.it) P.I. 00934960352 - P.I.00934960352 Registro A.E.E. IT8020000002833