

FREEZER 400



Characteristics

Structure	White or Stainless steel 18/10 int.+ext.
Insulation thickness	50 (polyur. mm)
Doors number	1
Door type	Fully Insulated
Refrigeration type	Ventilated
Refrigerant type	R404A
Temperature range	-10° -25°
Temperature control/adjustment	ECT-F Control: with Hi/Low Temp. alarm, door ajar, ON/OFF w/password
Defrosting type	Auto
Voltage	230V/1/50Hz
Capacity (LT)	400
Shelves nr.	suggested 4
Width (cm)	60
Depth (cm)	60
Height (cm)	189
Net weight (kg)	90
Equipment in accordance with	ECC directives: 98/37/CE, 2006/95/CE, 2004/108/CE, 93/42/CE
Internal cabinet with shelves/drawers interchangeable	

Accessories

Additional open wire shelf realized in sheet steel plastic coated	Automatic water evaporation tray
Drawer realized in aluminium	Frequency 60Hz
Safety key locking	Voltage 115V
Kit of castors with brakes	DMLP Digital Monitor (Alarm System)
PT100 sensor	Accessories for DMLP Digital Monitor: - DMLP Printer (Graphic Temp. Printer) - DMLP Remote panel - Ext. terminal board for RS485/dry contacts -DMLP PT100 Extension module + nr.1 PT100 + 4-20mA output - WEB LIGHT SERVER module (Ethernet) - GSM Communicator CF2008 module



At any time, the manufacturer may bring modifications to the model above described, for technical or commercial reasons. The picture does not necessary shows the product in the standard version.