



Cold in a perfect combination of Design,
Quality and Professionalism for the Medical field.

FREEZER 700



Characteristics

Structure	White or Stainless steel 18/10 int.+ext.
Insulation thickness	60 (polyur. mm)
Doors number	1
Door type	Fully Insulated
Shelves nr.	suggested 3
Refrigeration type	Ventilated
Refrigerant type	R404A
Temperature range	-10° -25°
Temperature control/adjustment	ECT-F Control® : with Hi/Low Temp. alarm, door ajar, ON/OFF w/password
Defrosting type	Auto
Voltage	230V/1/50Hz
Capacity (LT)	700
Internal lighting	standard fitted
Width (cm)	72
Depth (cm)	80
Height (cm)	205
Net weight (kg)	150
Equipment in accordance with	Directives 98/37/CE, 2006/95/CE, 2004/108/CE, 93/42/CE and following modifications
Internal cabinet with shelves/drawers interchangeable	

Accessories

Additional open wire shelf realized in sheet steel plastic coated	Interchange Rack System for Shelves/Baskets
Drawer realized in aluminium	Internal steel wire basket
Safety key locking	Automatic water evaporation tray
Kit of castors with brakes	Frequency 60Hz
PT100 sensor	Voltage 115V
WEB LIGHT SERVER (Rete Ethernet + GSM)	DMLP Digital Monitor (Alarm System)®
GSM Communicator CF2008 module	Accessories for DMLP Digital Monitor® :
	- DMLP Printer (Graphic Temp. Printer)
	- DMLP Remote panel
	- Ext. terminal board for RS485/dry contacts
	-DMLP PT100 Extension module + nr.1 PT100 + 4-20mA output

At any time, the manufacturer may bring modifications to the model above described, for technical or commercial reasons. The picture does not necessary shows the product in the standard version.



CF di Ciro Fiocchetti & C. s.n.c. via Lorenzini, 53 - 42045 Luzzara (RE) Italy -

Tel. +39 0522 976232 - Fax +39 0522 976028 - Web site: www.fiocchetti.it - E-mail: info@fiocchetti.it P.I. 00934960352 - P.I.00934960352 Registro A.E.E. IT8020000002833