

SLEE
M A I N Z



Rotary Microtome CUT 6062

Precise full automation in modular design



Rotary Microtome CUT 6062

Precise full automation in modular design



Standard unit for paraffin sections and research-, plastic- and industrial applications. The fully motorised unit offers an even greater comfort than manual and semi-automatic microtomes whilst retaining all essential features of this series. Additional features are:

- ▶ *Motor drive*
- ▶ *Footswitch*
- ▶ *Emergency stop*
- ▶ *Operating pad for motorised cutting*
- ▶ *Operating pad for motorised advance / return*
- ▶ *Individual or series cutting*
- ▶ *Advance automatic in 2 speeds*
- ▶ *Specimen final position can be selected, top or bottom*
- ▶ *Specimen size up to 50 x 50 mm with standard object clamp or standard cassette size for universal cassette clamp*
- ▶ *Motorized cutting steplessly adjustable*
- ▶ *Speed for cutting and returning specimen can be adjusted seperately*
- ▶ *Universal power unit 100 – 240 V, 50/60 Hz*
- ▶ *The equipment is supplied completely useable including:*
 - *Object orientation unit alternatively fixed*
 - *Universal cassette clamp alternatively standard object clamp*
 - *Knife holder base with disposable blade holder low profile or high profile alternatively standard knife holder*
 - *Section waste tray*



The operating pad for advance / retraction, slow motion, cutting thickness adjustment and trimming



CUT 4062 – manual model



Technical Data	
Range of thickness	0,5 µm – 100 µm
Increments	0,5 µm from 0,5 µm – 2,0 µm 1,0 µm from 2,0 µm – 10 µm 2,0 µm from 10 µm – 50 µm 5,0 µm from 50 µm – 100 µm
Horizontal specimen advance	28 mm
Vertical stroke	60 mm
Specimen orientation	XY-Axes: 8°, Z-Axes: 360°
Cutting speed	steplessly adjustable from 3 – 300 mm/sec
Advance for trimming	adjustable from 0 – 300 µm, free programmable
Weight and Dimensions	
Dimensions (in mm)	Depth x Width x Height 495 x 400 x 290
Dimensions packed (in mm)	650 x 550 x 480
Weight net	29 kg
Weight packed	41 kg
Electrical parameters	Art.-No. 1080001 230 V / 50 Hz Art.-No. 1081001 230 V / 60 Hz Art.-No. 1082001 115 V / 60 Hz Art.-No. 1083001 100 V / 50 Hz Art.-No. 1084001 100 V / 60 Hz
Please ask for other units for Histopathology and consumables as well as laminar flow equipment.	



Connect With Us

