

EMOTECA 1500 LUX



Characteristics

| | |
|---|--|
| Structure | White or Stainless steel 18/10 int. +ext. |
| Insulation thickness | 70 (polyur. mm) |
| Doors number | 2 |
| Door type | Glass |
| Refrigeration type | Ventilated |
| Refrigerant type | R134A |
| Temperature range | +4° |
| Temperature control/adjustment | ECT-F Control® : with Hi/Low Temp. alarm, door ajar, ON/OFF w/password |
| Defrosting type | Auto |
| Voltage | 230V/1/50Hz |
| Capacity (LT) | 1500 |
| Internal lighting | standard fitted |
| DMLP Digital Monitor (Alarm System) | standard fitted |
| DMLP Printer (Graphic Temp. Printer) | standard fitted |
| Drawers nr. | 14 |
| Storage capacity (blood bags nr., 450 ml) | 672 |
| Width (cm) | 144 |
| Depth (cm) | 82 |
| Height (cm) | 205 |
| Net weight (kg) | 180 |
| Equipment in accordance with | Directives 98/37/CE, 2006/95/CE, 2004/108/CE, 93/42/CE and following modifications |

Available also with fully insulated door.
Automatic water evaporation.

Cooling unit of monoblock type with compact evaporator ceiling mounted for a bigger internal capacity of the refrigerated cabinet

Accessories

| | |
|--------------------------------|--|
| Safety key locking | Frequency 60Hz |
| Drawer perspex front (H=83 mm) | Voltage 115V |
| Kit of castors with brakes | DMLP Remote panel |
| PT100 sensor | Ext. terminal board for RS485/dry contacts |
| | Probe for liquid simulation |
| | DMLP PT100 Extension module + nr.1 PT100 + 4-20mA output |
| | WEB LIGHT SERVER (Ethernet + GSM) |
| | GSM Communicator CF2008 module |

At any time, the manufacturer may bring modifications to the model above described, for technical or commercial reasons. The picture does not necessary shows the product in the standard version.