

## EMOTECA 700 ECT-F TOUCH



go to ECT-F version

### Characteristics

<b>Temperature Range</b>	+4 °C
<b>Capacity</b>	620 lt (21,91 cu ft) <a href="#">MORE INFO</a>
<b>Blood bags capacity (450 ml)</b>	336
<b>External Dimensions (W x D x H)</b>	cm 72 x 82,5 x 205 <a href="#">MORE INFO</a>
<b>Structure and Insulation</b>	sanitized pre-coated steel with bacteriostatic activity, white colour- in/out (rust- corrosion-proof material), or stainless steel 18/10 AISI 304 inside and sanitized pre-coated steel white colour- outside; insulation polyurethane thickness 60 mm
<b>Door</b>	Nr 1 glass door with triple glass panels
<b>Electric Digital Key Lock</b>	<a href="#">MORE INFO</a>
<b>Height adjustable Feet</b>	
<b>Light</b>	Led type with adjustable brightness
<b>Internal equipment</b>	nr.7 extractible aluminum drawers mounted on telescopic slides <a href="#">MORE INFO</a>
<b>Controller</b>	ECT-F TOUCH + DMLP TOUCH DIGITAL MONITOR <a href="#">MORE INFO</a>
<b>Alarms</b>	Acoustic and Visual for temperature deviations, power failure and faults, with automatic recording even in case the electricity is off
<b>Safety Thermostat</b>	
<b>Data and Event recording</b>	10 years on SD card; 1 year on Flash-memory
<b>Temperature Graph</b>	A customizable real time graphic always visible from the home page.
<b>Connectivity</b>	USB-SD-SIM port with frontal access ; external board for Dry Contact and Serial ports RS485 and RJ45
<b>Refrigeration Type</b>	Forced-air, ventilated
<b>Defrost</b>	Automatic with automatic evaporation of the condensate water
<b>Probe for product simulation</b>	

### Technical data

<b>Details</b>	<a href="#">MORE INFO</a>
<b>In accordance with</b>	93/42/CE - class IIa regulation, and following modifications
<b>Package</b>	Strong Cardboard on wooden pallet <a href="#">MORE INFO</a>
<b>note</b>	<ul style="list-style-type: none"><li>• DIN 58371 conformity</li><li>• Available also in TWIN version (double compressor)</li></ul>

## Accessories

Blind Door

Castors with brakes

Extractible Aluminum Drawer with partitions

Plexiglas front for drawers

Wire basket in stainless steel H mm 148

S/Steel Rack cm 14 x 50 x 15 H (max nr.3 each shelf)

GSM Module [MORE INFO](#)

Wi-fi Module [MORE INFO](#)

White coated sheet shelf

Cable port mm 35 with cap

Cable port mm 15

Humidity Sensor

PT100 probe (free contacts)

Voltage stabilizer

4-20mA converter module [MORE INFO](#)

60 Hz Frequency

115 V

Wooden crate Package

---



Connect With Us

