

Thermolyne
Dri-Baths™



Fixed Block



Type DB12200 and DB5900

Simple Operation!

- Calibrated with NIST Standard
- Choice of 10, 20 or 40 wells
- Anodized aluminum block provides maximum heat transfer



Product Description

- Anodized aluminum heating block provides excellent heat transfer to your test tubes for maximum uniformity and reliable results.
- Baked-on enamel finish resists harsh chemicals and hard usage.
- Type DB5900 cradle design permits tube rocking for sample agitation.
- Type DB5900 numbered wells allow for easy test tube identification.
- Clear acrylic side windows on Type DB5900 permit observation of colormetric changes.

Operation

- Versatile operating range of ambient +5°C to 60°C, ± 0.5°C. Just dial in the desired temperature.
- No need to unplug; designed for continuous use.
- Test tubes and cuvettes stay dry during incubations to eliminate mess and contamination.

Applications for All Models

- General sample incubation
- Coombs tests
- Compatibility and antibody testing
- Immunohematologic incubating
- RIA-aldosterone incubating
- Blood chemistries
- Blood crossmatching tests
- Typing

Applications Model DB5900

- Colormetric tests
- Coagulation studies
- VDRL Test
- Activated clotting times
- Serology procedures
- Urine and blood cultures

PRODUCT SPECIFICATIONS

| Type | Well Dimensions (mm) | | Overall Dimensions Inches (cm) | | | Shipping Weight Lb. (kg) |
|---------|----------------------|-------|--------------------------------|------------|------------|--------------------------|
| | Diameter | Depth | W | H | D | |
| DB5900 | 13 | 51 | 9.0 (22.8) | 3.13 (7.9) | 2.13 (5.4) | 2.5 (1.1) |
| DB12200 | 12.7 | 27 | 8.75 (22.2) | 3.25 (8.2) | 4.5 (11.4) | 5.25 (2.3) |

ORDERING INFORMATION

| Model # | Volts | Electrical (50/60 Hertz) Amps | Watts | Standard Calibration | Tube Size mm | # of Wells |
|----------------------------|-------|-------------------------------|-------|----------------------|--------------|------------|
| DB5915E ^{1,2} | 120 | 1.0 | 120 | 37°C | 13 | 10 |
| DB5910E | 240 | 0.5 | 120 | 37°C | 13 | 10 |
| DB5920E | 240 | 0.19 | 45 | 37°C | 13 | 20 |
| DB5925E ^{1,2} | 120 | 0.38 | 47 | 37°C | 13 | 20 |
| DB12215E ^{1,2} | 120 | 0.33 | 40 | 37°C | 12 | 40 |
| DB12215E-60 ^{1,2} | 125 | 0.4 | 47 | 37°C | 12 | 40 |

¹ CSA
² CE

Connect With Us

