

Characteristics



Structure	White or Stainless steel 18/10 int.+ext.
Insulation thickness	70 (polyur. mm)
Doors number	2
Door type	Glass
Refrigeration type	Ventilated
Refrigerant type	R134A
Temperature range	+4°
Temperature control/adjustment	ECT-F Control® : with Hi/Low Temp. alarm, door ajar, ON/OFF w/password
Defrosting type	Auto
Voltage	230V/1/50Hz
Capacity (LT)	1500
Internal lighting	standard fitted
DMLP Digital Monitor (Alarm System)	standard fitted
DMLP Printer (Graphic Temp. Printer)	standard fitted
Drawers nr.	14
Storage capacity (blood bags nr., 450 ml)	672
Width (cm)	144
Depth (cm)	82
Height (cm)	205
Net weight (Kg)	180
Equipment in accordance with	Directives 2006/42/CE, 2006/95/CE, 2004/108/CE and following modifications

Available also with fully insulated door.
Automatic water evaporation.

Cooling unit of monoblock type with compact evaporator ceiling mounted for a bigger internal capacity of the refrigerated cabinet

Accessories

Safety key locking

Drawer perspex front (H=83 mm)

Kit of castors with brakes

PT100 probe

Frequency 60Hz

Voltage 115V

DMLP Remote panel

Ext. terminal board for RS485/dry contacts

Probe for liquid simulation

DMLP PT100 Extension module + nr.1 PT100 + 4-20mA output

WEB LIGHT SERVER (Ethernet + GSM)

GSM Communicator CF2008 module

Connect With Us

