



Cold in a perfect combination of Design,
Quality and Professionalism for the Medical field.

FREEZER 1500



Characteristics

Structure	White or Stainless steel 18/10 int.+ext.
Insulation thickness	70 (polyur. mm)
Doors number	2
Door type	Fully Insulated
Shelves nr.	suggested 6
Refrigeration type	Ventilated
Refrigerant type	R404A
Temperature range	-10° -25°
Temperature control/adjustment	ECT-F Control® : with Hi/Low Temp. alarm, door ajar, ON/OFF w/password
Defrosting type	Auto
Voltage	230V/1/50Hz
Capacity (LT)	1500
Width (cm)	144
Depth (cm)	82
Height (cm)	210
Net weight (kg)	200
Equipment in accordance with	Directives 98/37/CE, 2006/95/CE, 2004/108/CE, 93/42/CE and following modifications
Automatic condensate water evaporation.	
Internal cabinet with shelves/drawers interchangeable	

Accessories

Additional open wire shelf realized in sheet steel GSM Communicator CF2008 module
plastic coated
Drawer realized in aluminium
Safety key locking
Kit of castors with brakes
PT100 sensor
WEB LIGHT SERVER (Rete Ethernet + GSM)

Interchange Rack System for Shelves/Baskets
Internal steel wire basket
Frequency 60Hz
Voltage 115V
DMLP Digital Monitor (Alarm System)®
Accessories for DMLP Digital Monitor® :
- DMLP Printer (Graphic Temp. Printer)
- DMLP Remote panel
- Ext. terminal board for RS485/dry contacts
-DMLP PT100 Extension module + nr.1 PT100 +
4-20mA output