

4-20mA converter module

60 Hz Frequency

115 V

Wooden crate Package

## Refrigerator MEDIKA 100 ECT-F



go to ECT-F TOUCH version

### Characteristics

<b>Temperature Range</b>	+2 / +15 °C
<b>Capacity</b>	96 lt (3,40 cu ft) <a href="#">MORE INFO</a>
<b>External Dimensions (W x D x H)</b>	cm 52 x 63,5 x 71 <a href="#">MORE INFO</a>
<b>Structure and Insulation</b>	sanitized pre-coated steel with bacteriostatic activity, white colour- in/out (rust- corrosion-proof material); insulation polyurethane thickness 40 mm
<b>Feet</b>	n.4 stabilizing feet
<b>Door</b>	Nr 1 glass door with triple glass panels
<b>Light</b>	Led type
<b>Suggested internal fittings</b>	nr.1 shelf <a href="#">MORE INFO</a>
<b>Controller</b>	ECT-F <a href="#">MORE INFO</a>
<b>Alarms</b>	Acoustic and Visual for temperature deviations and failures
<b>Data and Event recording</b>	last 12 events available from display
<b>Refrigeration Type</b>	Forced-air, ventilated
<b>Defrost</b>	Automatic with automatic evaporation of the condensate water

### Technical data

<b>Details</b>	<a href="#">MORE INFO</a>
<b>In accordance with</b>	2006/42/CE, 2006/95/CE, 2004/108/CE, 93/42/CE and following modifications
<b>Package</b>	Strong Cardboard on wooden pallet <a href="#">MORE INFO</a>

### Accessories

Key Lock

Rollers

Castors with brakes

Additional Shelf

Extractible Aluminum Drawer with partitions

Plexiglas front for drawers

Wire basket in stainless steel H mm 148

Dry Contact

DMLP DIGITAL MONITOR [MORE INFO](#)

DMLP PRINTER

Cable port mm 15

Humidity Sensor

PT100 probe (free contacts)

Voltage stabilizer

4-20mA converter module

60 Hz Frequency

115 V

Wooden crate Package



### Connect With Us

