

## MEDIKA 700 LUX



### Characteristics

Structure	White or Stainless steel 18/10 int. +ext.
Insulation thickness	60 (polyur. mm)
Doors number	1
Door type	Glass
Refrigeration type	Ventilated
Refrigerant type	R134A
Temperature range	+2° +15°
Temperature control/adjustment	ECT-F Control® : with Hi/Low Temp. alarm, door ajar, ON/OFF w/password
Defrosting type	Auto
Voltage	230V/1/50HZ 220V/1/60HZ
Capacity (LT)	700
Internal lighting	standard fitted
Shelves nr.	suggested 3
Width (cm)	72
Depth (cm)	83
Height (cm)	205
Net weight (kg)	130
Equipment in accordance with	Directives 98/37/CE, 2006/95/CE, 2004/108/CE, 93/42/CE and following modifications

Cooling unit of monoblock type with compact evaporator ceiling mounted for a bigger internal capacity of the refrigerated cabinet  
Automatic condensate water evaporation.  
Internal cabinet with shelves/drawers interchangeable

### Accessories

Additional open wire shelf realized in sheet steel plastic coated	PT100 sensor
Drawer realized in aluminium	WEB LIGHT SERVER (Rete Ethernet + GSM)
Safety key locking	GSM Communicator CF2008 module
Kit of castors with brakes	Interchange Rack System for Shelves/Baskets
Inner electrical sockets	Internal steel wire basket
Cable port	Voltage 115V
Humidity measuring sensor	DMLP Digital Monitor (Alarm System)® Accessories for DMLP Digital Monitor® : - DMLP Printer (Graphic Temp. Printer) - DMLP Remote panel - Ext. terminal board for RS485/dry contacts -DMLP PT100 Extension module + nr.1



PT100 + 4-20mA output

---

At any time, the manufacturer may bring modifications to the model above described, for technical or commercial reasons. The picture does not necessary shows the product in the standard version.

---

CF di Ciro Fiocchetti & C. s.n.c. via Lorenzini, 53 - 42045 Luzzara (RE) Italy -  
Tel. +39 0522 976232 - Fax +39 0522 976028 - Web site: [www.fiocchetti.it](http://www.fiocchetti.it) - E-mail: [info@fiocchetti.it](mailto:info@fiocchetti.it) P.I.  
00934960352 - P.I.00934960352 Registro A.E.E. IT8020000002833