

Ordering Information – Standard Glass Microfiber Extraction Thimbles

Dimensions (mm)*	Wall Thickness (mm)	Catalog Number	Quantity/Pack
Grade 603 g (Glass Fiber with Inorganic Binder)			
10 × 38	1.5	10371103	25
16 × 50	1.0	10371005	25
19 × 90	1.0	10371007	25
22 × 80	1.5	10371011	25
23.8 × 68	1.5	10371114	25
25 × 98	1.5	10371029	25
25 × 100	1.5	10371019	25
26 × 63	1.5	10371122	25
26 × 100	1.5	10371023	25
28 × 60	1.5	10371025	25
30 × 100	1.5	10371036	25
33 × 94	1.5	10371042	25
33 × 100	1.5	10371043	25
33 × 118	1.5	10371045	25
35 × 150	1.5	10371055	25
44 × 230	1.5	10371075	25
Glass Microfiber Thimbles (without Binder)			
25 × 80	-	2811-258	25
30 × 80	-	2811-308	25

* Internal diameter and external length

Benchkote and Benchkote Plus

Benchkote

Benchkote is an absorbent, impermeable material designed to protect laboratory surfaces against hazardous spills. The material features a high-quality, smooth, absorbent Whatman paper, which quickly absorbs liquid spills, and a laminated polyethylene layer that prevents flow through to the working surface. After use, the sheet is incinerated or disposed of according to local regulations.



Benchkote Plus

Benchkote Plus™ is a thicker, more absorbent material for more demanding applications and can absorb in excess of 0.75 liters of water per square meter.

Features and Benefits

- Material is very strong, making it tear resistant, wet or dry
- Smooth white surface can be written on with ink or pencil and lies flat
- Suitable for saturation with disinfectant to protect benches where pathogens and other bacteria are present
- Use polyethylene side up to collect deposits without absorption
- Paper side quickly absorbs liquid spills, preventing liquids from going through to the work surface

- Spillages are trapped in the absorbent paper
- Benchkote can be incinerated after use; the polyethylene layer does not melt or drip but is rapidly consumed in the flames

Applications

- Containing radiochemical spillage and avoiding contamination
- Recovering spillage of expensive materials
- Protecting hard surfaces to lessen impact
- Water or solvent wick for humidity chambers
- Lining of chemical cabinets, laboratory bench drawers, and laboratory hoods

Ordering Information – Benchkote for Blotting

Dimensions (mm)	Catalog Number	Description	Quantity/Pack
Benchkote Surface Protector			
460 × 570	2300-594*	Pad	1 (50 sheets)
460 × 570	2300-599	Pad	1 (50 sheets)
460 × 570	2300-916	Sheets	50
460 × 570	2300-917	Sheets	100
460 mm × 50 m	2300-731	Reel	1
920 mm × 50 m	2300-772	Reel	1
Benchkote Plus Surface Protector			
500 × 600	2301-6150	Sheets	50
600 mm × 50 m	2301-6160	Reel	1

* Product is only available in the U.S.



Connect With Us

