

SIRIUS

Microincinerator

A Microincinerator you can touch!

Meet new safety regulations with a revolutionary Microincinerator!



- **WORK WITH GLOVES**
- **MULTIPLE USE**
- **USER SAFETY**

■ Sterilization

After reaching a sterilization temperature of around 1000°C, loop and needle are sterilized in 2-4 seconds.

■ Supports Working with Gloves

With its unique design the temperature of the exterior surface does not exceed 30°C.*

■ Sterilization in quartz tube

Prevents aerosol formation

■ User Safety

Heater resistance running with 12V



Slide fixation



Loop sterilization



You can safely touch the exterior surface during operation

* When the device is operated in still air and at room temperature

New safety regulations have meant that Microincinerators are increasingly replacing the traditional Bunsen burners that have long been fundamental to microbiology laboratories. Accordingly, CDC and WHO recommend using microincinerators in laboratories instead of Bunsen burners.

Microorganisms taken from liquid cause formation of aerosol in Bunsen Burner applications. Since this process is carried out in quartz tube in the Sirius micro Incinerator aerosol formation is completely inhibited.

When using biosafety cabinets contrary to bunsen burners, the filter system is not damaged and cabinet air flow not affected.

Features & Advantages

- During operation the exterior surface temperature of the device is 30°C*
- Maximum user security with heater resistance of 12V
- Suitable for slide fixation and sterilization of culture tubes
- Energy and environment-friendly design and minimum ensures power consumption
- Operational adjustment as 270°

Technical Specification

Main Input Voltage : 210-230V, 50 Hz

Heater Operating Voltage: ~11,5V Max.

Energy Consumption : 0.150 kw/h

Quartz Glass Tube Dimensions : Ø 18 mm, length:100 mm

Sterilization Temperature: 850°C – 1100°C

Time to Reach Sterilization Temperature : 7-9 min.

Sterilization Duration : 2-4 seconds

Surface Temperature of Device during Operation: 30°C *

Weight : 3100 gr

Dimensions : W150 x D250 x H 215 mm



Connect With Us



* When the device is operated in still air and at room temperature 23°C.