




## PP Fume Hood




LED Display



Waterproof Socket



PP Sink  
resistant to acid,  
alkali and anti-corrosion



Water&Gas  
Remote Control

## ADVANTAGE

1. It is safer to use anti-corrosive water tap.
2. Microprocessor control system, LED display.
3. With memory function in case of power-failure.
4. Made of porcelain white PP, resistant to acid, alkali and anti-corrosion.
5. Front window which is made of thick transparent toughened glass maximize light and visibility inside the fume hood, providing a bright and open working environment.

## TECHNICAL PARAMETERS

Model	FH1000(P)	FH1200(P)	FH1500(P)	FH1800(P)
External Size (W*D*H)	1040*750*2200mm	1240*800*2200mm	1540*800*2200mm	1840*800*2200 mm
Internal Size (W*D*H)	820*520*872mm	1020*570*872mm	1320*570*872mm	1620*570*872 mm
Work Surface Height	740mm			
Max Opening	815mm			
Air Velocity	0.4~0.6m/s			
Noise	≤60dB			
Illuminating Lamp	LED lamp	Fluorescent Lamp	Fluorescent Lamp	Fluorescent Lamp
	12W*1	30W*2	30W*2	30W*2
Blower	Built-in axial flow blower; Speed adjustable; resistant to acid, alkali.			
Front Window	Manual, 5mm toughened glass, height adjustable.			
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz			
Consumption	330W	360W	360W	360W
Material	Main Body	Made of Porcelain white PP, thickness 8mm, resistant to strong acid, alkali and anti-corrosion		
	Work Table	Chemical resistant phenolic resin		
Standard Accessory	Illuminating lamp, Water tap, Gas tap, Water Sink, Base cabinet			
	Waterproof socket*2 4 meters PVC duct, Diameter: 250mm			
Optional Accessory	PP work table, epoxy resin board or ceramic board. Outer centrifugal blower, resistant to strong acid, alkali.			
Gross Weight	160kg	198kg	225kg	259kg
Package Size (W*D*H)	Main Body	1120*840*1620mm	1320*880*1620mm	1620*880*1620mm
	Base Cabinet	1120*790*1040mm	1620*880*1040mm	1610*880*1040mm