HI 83214

C 214 - A Complete System for Waste Water Analysis

The new **HI 83214** multi-parameter photometer is a compact instrument featuring different ranges and methods, suitable for a wide range of applications.

HI 83214 is designed and built to perform COD analysis in accordance with EPA 410.4 and ISO 15705:2002 standards.

Ensuring accurate and repeatable results, it is the ideal tool for documenting water treatment processes.

Besides the fundamental parameter of C.O.D., **HI 83214** also measures total ammonia nitrogen and total reagent phosphorus.

The instrument can be connected to a PC through an RS232 serial port and all stored measurements can be downloaded to a PC using **HANNA** instru ments[°]/ **HI 92000** software.

HI 83214, allows a complete wastewater analysis with a single powerful instrument.

> 3 tungsten lamps with narrow band interference filter 420/525/610 nm

> > **4 Silicon Photocells**

after 10 minutes of non-use

0 to 50°C (32 to 122°F);

RH max 95% non-condensing

230 x 165 x 70 mm / 640 g

2 x 9V battery or 12 Vdc adapter



Parameter	Range	Method	Reagent Code
Ammonia, LR	0.00 to 3.00 mg/L	Nessler	HI 93764A-25
Ammonia, HR	0 to 100 mg/L	Nessler	HI 93764B-25
Chlorine, Free	0.00 to 5.00 mg/L	DPD	HI 93701-01, HI 93701-03
Chlorine, Total	0.00 to 5.00 mg/L	DPD	HI 93711-01, HI 93711-03
Nitrate	0.0 to 30.0 mg/L	Chromotropic acid	HI 93766-50
Nitrogen, Total	0.0 to 25.0 mg/L	Chromotropic acid	HI 93767A-50
Nitrogen, Total HR	10 to 150 mg/L	Chromotropic acid	HI 93767B-50
COD LR, EPA*	0 to 150 mg/L	Dichromate	HI 93754A-25
COD MR, EPA*	0 to 1500 mg/L	Dichromate	HI 93754B-25
COD HR	0 to 15000 mg/L	Dichromate	HI 93754C-25
COD LR, Mercury-free***	0 to 150 mg/L	Dichromate, mercury-free	HI 93754D-25
COD MR, Mercury-free***	0 to 1500 mg/L	Dichromate, mercury-free	HI 93754E-25
COD LR, ISO**	0 to 150 mg/L	Dichromate	HI 93754F-25
COD MR, ISO**	0 to 1000 mg/L	Dichromate	HI 93754G-25
Phosphorus, Reactive	0.00 to 5.00 mg/L	Ascorbic acid	HI 93758A-50
Phosphorus, Acid Hydrolyzable	0.00 to 5.00 mg/L	Ascorbic acid	HI 93758B-50
Phosphorus, Total	0.00 to 3.50 mg/L	Ascorbic acid	HI 93758C-50
Phosphorus, Reactive HR	0.0 to 100.0 mg/L	Vanadomolybdophosphoric acid	HI 93763A-50
Phosphorus, Total HR	0.0 to 100.0 mg/L	Vanadomolybdophosphoric acid	HI 93763B-50
Notes:			

* Method with chromium-sulphuric acid is officially recognized by EPA for wastewater analysis.

** The HI 93754F-25 and HI 93754G-25 method follows the official method ISO 15705.

*** This method is recommended for general purpose analysis with no chloride interference

Accessories

HI 92000 HI 920010 Windows[®] compatible software Serial cable for PC connection

- HI 3898 Test kit for Chloride interference

K79

For a comprehensive list of accessories, see sections U and V



HI 83214 is supplied complete with 5 cuvets, 1

cuvet-holder, batteries, 12 Vdc adapter and



Specifications Light Source

Light Detector

Power Supply

Environment

Dimensions / Weight

instructions

Ordering Information

Auto-off

Connect With Us

Y 🖸

Photometers