

witeg® Aluminum-case Heating Mantles, “WHM”, with Controller, 50~20,000ml, 450°C

For Spherical Flask, with Nickel Chrome Heating Element, Built-in Temperature Controller, with Certi. & Traceability

- with Certificate & Traceability : Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
- Full Choices of Vessel, Capacity, Housing and Control are Offered!
- **Nickel Chrome Heating Element - Coil Type** : Acid-Resistant, Long Life Time
- Built-in Temperature Controller
- All Kinds of Round Flasks can be used - DURAN/Kimax/Pyrex/Iwaki
- CE Certified

Catalog No.		Flask Capacity (ml)	Flask Dia. Φ(mm)	Watts (W)	Inside Depth (mm)	Mantle Outside Φ x H (mm)	Support Rod Φ x H (mm)	Application (Flask-brand)
with 230V	with 120V							
DH.WHM12010	DH.WHM12020	50	49 ~ 52	80	40	Φ 145 x H140	Φ 13 x H440	Common-Use
DH.WHM12011	DH.WHM12021	100	63 ~ 66	80	40	Φ 145 x H140	Φ 13 x H440	Common-Use
DH.WHM12012	DH.WHM12022	250	83 ~ 86	140	50	Φ 145 x H140	Φ 13 x H440	Common-Use
DH.WHM12013	DH.WHM12023	500	102 ~ 105	240	65	Φ 190 x H165	Φ 13 x H440	Common-Use
DH.WHM12014	DH.WHM12024	1,000	130 ~ 133	350	75	Φ 190 x H165	Φ 13 x H440	Common-Use
DH.WHM12015	DH.WHM12025	2,000	165 ~ 169	450	100	Φ 270 x H200	Φ 13 x H660	for DU./Iw.
DH.WHM120151	DH.WHM120251	2,000	161 ~ 164	450	100	Φ 270 x H200	Φ 13 x H660	for Ki./Py.
DH.WHM12016	DH.WHM12026	3,000	184 ~ 187	550	105	Φ 270 x H200	Φ 13 x H660	for DU./Ki.
DH.WHM12017	DH.WHM12027	5,000	221 ~ 224	800	131	Φ 325 x H226	Φ 13 x H800	Common-Use
DH.WHM12018	DH.WHM12028	6,000	234 ~ 237	800	131	Φ 325 x H226	Φ 13 x H800	for DU./Ki.
DH.WHM12019	DH.WHM12029	10,000 ☆	278 ~ 282	1400	150	Φ 390 x H240	Φ 13 x H800	for DU.
DH.WHM12070	DH.WHM12071★	20,000 ☆	344 ~ 348	2000	200	Φ 470 x H260	Φ 13 x H800	for DU.

☆-Marks 10.000ml & 20.000ml Mantle Steel-case / Magnetic Stirring is not Available

★Remarks : DU.: DURAN Ki.: Kimax Iw.: Iwaki Py.: Pyrex



witeg® Aluminum-case Stirrer Heating Mantles, “WHM”, 50~6,000ml, 450 °C, with Certi. & Traceability

For Spherical Flask, with Controller, Nickel Chrome Heating Element, Stirring & Temperature Controller, 50~750rpm

- with Certificate & Traceability : Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
- Full Choices of Vessel, Capacity, Housing and Control are Offered!
- **Nickel Chrome Heating Element - Coil Type** : Acid-Resistant, Long Life Time
- Built-in Temperature Controller
- All Kinds of Round Flasks can be used - DURAN/Kimax/Pyrex/Iwaki
- CE Certified

Catalog No.		Flask Capacity (ml)	Flask Dia. Φ(mm)	Watts (W)	Inside Depth (mm)	Mantle Outside Φ x H (mm)	Support Rod Φ x H (mm)	Application (Flask-brand)
with 230V	with 120V							
DH.WHM12030	DH.WHM12040	50	49 ~ 52	80	40	Φ 145 x H140	Φ 13 x H440	Common-use
DH.WHM12031	DH.WHM12041	100	63 ~ 66	80	40	Φ 145 x H140	Φ 13 x H440	Common-use
DH.WHM12032	DH.WHM12042	250	83 ~ 86	140	50	Φ 145 x H140	Φ 13 x H440	Common-use
DH.WHM12033	DH.WHM12043	500	102 ~ 105	240	65	Φ 190 x H165	Φ 13 x H440	Common-use
DH.WHM12034	DH.WHM12044	1,000	130 ~ 133	350	75	Φ 190 x H165	Φ 13 x H440	Common-use
DH.WHM12035	DH.WHM12045	2,000	165 ~ 169	450	100	Φ 270 x H200	Φ 13 x H660	for DU/Iw.
DH.WHM120351	DH.WHM120451	2,000	161 ~ 164	450	100	Φ 270 x H200	Φ 13 x H660	for Ki/Py.
DH.WHM12036	DH.WHM12046	3,000	184 ~ 187	550	105	Φ 270 x H200	Φ 13 x H660	for DU/Ki.
DH.WHM12037	DH.WHM12047	5,000	221 ~ 224	800	131	Φ 325 x H226	Φ 13 x H800	Common-use
DH.WHM12038	DH.WHM12048	6,000	234 ~ 237	800	131	Φ 325 x H226	Φ 13 x H800	for DU/Ki.

★2pcs of PTFE Magnetic Stirrer Bars Offered : Oval-Type, Φ6.0 x L15mm (CW.001.615) and Φ10 L25 (CW.001.625.10) one each

★Remarks : DU.: DURAN Ki.: Kimax Iw.: Iwaki Py.: Pyrex

★Available for Iwaki Flask 3000ml

Connect With Us