

# Rock'n Rollers

## Available in two models:

- Single Speed Model L-201
- Single Regulated Model L-202

## Both models provide:

- Gentle rocking while rolling, to keep samples in motion
- Rocking movement 35 degr.
- 14 stainless steel rotating bars 208 x 10 mm diam.
- Heart to heart distance of tubes 19,5 mm



## Single-speed Rock'n roller Model L-201

- Roller speed: 10 rpm
- Rocking-frequency: 5 Cy/min
- Dimensions: 320 x 310 x 190 mm
- Weight: 3,6 kg

### Ordering:

230V 50/60Hz. Cat.no. 20100  
115 V 50/60Hz. Cat.no. 20110



## Variable-speed Rock'n roller Model L-202

- Rolling Speed: from 5 to 25 rpm
- Extension Cable: 2 m for in-cabinet use
- Rocking-frequency: 2,5 to 12,5 Cy/min
- Temperature Range:  
in cooler or incubator 2 - 50°C
- Basic Unit:  
Dimensions: 320 x 310 x 190 mm  
Weight 3,6 kg
- Controller:  
Dimensions: 150 x 190 x 75 mm  
Weight 1,2 kg

### Ordering:

230V 50/60Hz. Cat.no. 20200  
115 V 50/60Hz. Cat.no. 20210

Connect With Us

