

## Model i.Series® PF48i Platelet Agitator

### Specifications

Application, Rating and Electrical Data		Dimensions and Construction	
Application	Provides continuous gentle agitation conditions required for the storage of platelet products	Exterior (w x h x d) in (mm)	18 x 15.25 x 14.5 / (458 x 388 x 369)
Storage Capacity	48 Random Bags / 16 Apheresis Bags	Overall Exterior (w x h x d) in (mm) (Includes alarm buzzer)	18.5 x 15.25 x 14.5 / (470 x 388 x 369)
Incubator Compatibility	PC900i / PC900h	Base Material	Galvannealed steel with bacteria-resistant powder coating
Electrical Power	100V 50/60Hz 115V 50/60Hz 230V 50/60Hz	Shelf	1 Stationary
Fuses	0.5A (100V and 115V, quantity 1) 0.3A (230V, quantity 2)	Drawers	7 Pull-out / removable 1.38" (35mm) between drawers
Maximum Current	0.4 FLA / 0.4 FLA / 0.25 FLA	Shelf/Drawer Material	Galvannealed steel - perforated and powder coated
Building Supply Rating	15 amp dedicated ground circuit	Label Holders	Standard - Accommodate magnetic or adhesive labels
Certification / Agency Listing	QPS (Certified to UL and CSA Standards)	Motion Alarm	Standard - adjustable volume and delay
Indoor/Outdoor Use	Indoor use only	Motor	Heavy-duty, ball-bearing, gear
Application Environment	Non-corrosive, non-flammable, non-explosive, 5°C to 35°C (41°F to 95°F)	Fan	Single
<b>Warranty</b>		Resin Rollers and Glides	Yes
Standard (US/Canada)	2 years parts, 1 year labor	Net Weight	51 lb (23 kg)
Outside US/Canada	Consult your local representative	Shipping Weight	61 lb (28 kg)
		Clearance Requirements	Minimum 1" (25mm) across sides and 0.5" (13mm) across front and back for unobstructed movement and ventilation (when installed in a corresponding Helmer platelet incubator). Minimum 2" (50mm) across sides and 0.5" (13mm) across front and back for unobstructed movement and ventilation (when installed in a stand-alone configuration).
		Options / Accessories	Label Holder Kit, Red Designated Drawer, Extended Warranty

