



MTS 2/4 digital



KS 130 basic



KS 130 control



KS 260 control



KS 501 digital

* without image

MTS 2/4 digital	KS 130 basic	KS 130 control	KS 260 basic*	KS 260 control	KS 501 digital
orbital	orbital	orbital	orbital	orbital	orbital
3 mm	4 mm	4 mm	10 mm	10 mm	30 mm
2 o. 4 microtiter plates	2 kg	2 kg	7,5 kg	7,5 kg	15 kg
35 / 13,2 W	45 / 10 W	45 / 10 W	45 / 10 W	45 / 10 W	70 / 19 W
100 %	100 %	100 %	100 %	100 %	100 %
0 – 1.100 min ⁻¹	80 – 800 min ⁻¹	80 – 800 min ⁻¹	20 – 500 min ⁻¹	10 – 500 min ⁻¹	0 – 300 min ⁻¹
scale	LED line	digital	LED line	digital	digital
∞ / 1 – 99 min	∞ / 5 – 50 min	∞ / 0 – 9 h 59 min	∞ / 5 – 50 min	∞ / 9 h 59 min	∞ / 0 – 56 min
185 x 320 x 105 mm	270 x 316 x 98 mm	270 x 316 x 98 mm	360 x 420 x 98 mm	360 x 420 x 98 mm	505 x 585 x 120 mm
2,7 kg	8,8 kg	9,8 kg	8,5 kg	8,8 kg	26 kg
5 – 40 °C	5 – 50 °C	5 – 50 °C	5 – 50 °C	5 – 50 °C	5 – 50 °C
IP 21	IP 21	IP 21	IP 21	IP 21	IP 21
–	–	RS 232 / analog	–	RS 232 / analog	–
3208000 / 3208001	2980000 / 2980001	2980100 / 2980101	2980200 / 2980201	2980300 / 2980301	2526400 / 2526401