

## Horizontal Laminar Flow Cabinet



**LED Display**  
Microprocessor control system,  
LED display



**Waterproof Socket**  
2 waterproof sockets are located  
in the top panel, for optimum  
convenience of using small  
devices inside the cabinet.



**Side Glass Window**  
The transparent side glass  
windows maximize light and  
visibility inside the cabinet,  
providing a bright and open  
working environment.

## TECHNICAL PARAMETERS

Model	BBS-H1100(Previous name: BBS-DDS)	BBS-H1500(Previous name: BBS-SDS)
External Size (W*D*H)	1060*800*1690mm	1460*800*1690mm
Internal Size (W*D*H)	1040*500*650mm	1440*500*650mm
Work Surface Height	750mm	
Display	LED Display	
Airflow Velocity	Average of 0.3~0.5m/s	
Material	Main Body: Cold-rolled steel with anti-bacteria powder coating Work Table: 304 stainless steel Side Windows: 5mm toughened glass, anti-UV	
Pre-Filter	Polyester fiber, washable	
HEPA Filter	99.999% efficiency at 0.3µm	
Noise	<60dB	
Fluorescent Lamp	21W*1	28W*1
UV Lamp	20W*1 Emission of 253.7 nanometers	30W*1
Consumption	320W	620W
Waterproof Socket	Two, total load≤500W	
Caster	Universal caster with leveling feet	
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz	
Standard Accessory	Fluorescent lamp, UV lamp*2, Base stand, Waterproof socket*2	
Gross Weight	150kg	179kg
Package Size (W*D*H)	1230*1000*1820mm	1630*1000*1820mm