



Vari-Mix and Speci-Mix Test Tube Rockers



Type M71000, Type M26100 & Type M48700

Product Description

- Reversible pad features one side for capped tubes up to 110 mm long; opposite side holds tubes of any length.
- A white silicon rubber friction grip pad contrasts specimens and labels for easy viewing.
- Capped tubes can be easily loaded/unloaded without turning off the rocker.
- Provides smooth mixing action for consistently uniform specimen suspension.

Constant and Variable Speed Models!

- Choose from fixed or adjustable angle
 - Holds 10mm to 30mm tube diameter sizes
 - Ideal for blood collection tubes
 - Smooth mixing action provides uniform specimen suspension
- ☆ 12 Month Warranty



Operation

- Vari-Mix (M48700) options include: adjustable speed motor performance, 2 to 20 rpm and adjustable mixing platform, from 1° - 48° angle.
- Speci-Mix and Half-Size Speci-Mix have a preset 18 rpm motor speed and a preset 48° angle mixing platform.

PRODUCT SPECIFICATIONS

Model #	Maximum Load Lbs (kg)	Speed Angle	Rocking Range	Tube Diameter and Capacity (# of tubes)	Overall Dimensions Inches (cm)			Shipping Weight lb. (kg)
					W	H	D	
Speci - Mix								
M26125	1.25 (0.56)	Fixed 18 rpm	Fixed 48°	10 - 20 mm: 16 22 - 30 mm: 7	13.8(34.9)	4.3(10.7)	5.5(13.9)	5.3 (2.3 kg)
M26120-33	1.25 (0.56)	Fixed 18 rpm	Fixed 48°	10 - 20 mm: 16 22 - 30 mm: 7	13.8(34.9)	4.3(10.7)	5.5(13.9)	5.3 (2.3 kg)
Ambient Conditions: 4° to 40°C; 20 to 80% RH non-condensing								
Half Size Speci - Mix								
M71015	1.25 (0.56)	Fixed 18 rpm	Fixed 48°	10 - 20 mm: 8 22 - 30 mm: 3	7.5(19.1)	4.3(10.7)	5.5(13.9)	3.0 (1.4)
M71010-33	1.25 (0.56)	Fixed 18 rpm	Fixed 48°	10 - 20 mm: 8 22 - 30 mm: 3	7.5(19.1)	4.3(10.7)	5.5(13.9)	3.0 (1.4)
Ambient Condition: 4° to 40°C; 20 to 80% RH non-condensing								
Vari - Mix								
M48725		Adjustable 2 to 20 rpm	Adjustable 1° to 48	10 - 20 mm: 16 22 - 30 mm: 7	15.0(38.1)	4.3(10.7)	5.5(13.9)	5.8 (2.6)
M48720-33		Adjustable 2 to 20 rpm	Adjustable 1° to 48	10 - 20 mm: 16 22 - 30 mm: 7	15.0(38.1)	4.3(10.7)	5.5(13.9)	5.8 (2.6)
Rocking Angle: Adjustable 1 to 48, Ambient Condition: 4° to 40°C; 20 to 80% RH non-condensing								

ORDERING INFORMATION

Model #	Volts	Amps	Hz	Model #	Volts	Amps	Hz
M26125 ¹	120	0.3	50/60	M71010-33 ^{1,2}	220-240	0.01	50
M26120-33 ^{1,2}	220-240	0.01	50	M48725	120	0.08	50
M71015	120	0.03	50/60	M48720-33 ^{1,2}	220-240	0.02	50

CSA, CE