


Vertical Laminar  
Flow Cabinet  
---Double Sides Type



**LED Display**  
Microprocessor control system, LED display



**UV Lamp**  
Emission of 253.7 nanometers for most efficient decontamination



**Double Sides**  
Double sides work bench, operators can sit face to face

## ADVANTAGE

Double sides work bench, 2~4 operators can work together.

## TECHNICAL PARAMETERS

Model	BBS-DSC	BBS-SSC
External Size (W*D*H)	1040*660*1770mm	1440*660*1770mm
Internal Size (W*D*H)	940*560*545mm	1340*560*545mm
Work Surface Height	750mm	
Display	LED Display	
Airflow Velocity	Average of 0.3~0.5m/s	
Material	Main Body: Cold-rolled steel with anti-bacteria powder coating Work Table: 304 stainless steel	
Pre-Filter	Polyester fiber, washable	
HEPA Filter	99.999% efficiency at 0.3µm	
Noise	<60dB	
Front Window	Manual, 5mm toughened glass, anti-UV	
Max Opening	350mm	
UV Lamp	18W*1 Emission of 253.7 nanometers	30W*1
Fluorescent Lamp	21W*1	28W*1
Consumption	350W	600W
Caster	Universal caster with leveling feet	
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz	
Standard Accessory	Fluorescent lamp, UV lamp*2, Base stand	
Gross Weight	150kg	174kg
Package Size (W*D*H)	1190*890*1340mm	1590*890*1340mm