

**Thermo Scientific® 2834 Precision® Model 282 General-Purpose Water Bath with Digital Controller & Digital Temperature Display, 5.5-Liter Capacity, Range: Ambient to 99.9°C, Resolution: 0.1°C, 230V/50Hz**



Microprocessor control with bright three-digit led temperature readout

SeamLess-stainless steel interior chamber is resistant to corrosion and has a 5.5L (1.5gal) capacity  
High-performance bath maintains water temperature from ambient to 99.9°C

Electrical requirement is 230V

This Thermo Scientific® ELED Precision® general-purpose water bath has digital control, digital temperature display and a 5.5L (1.5gal) capacity. It is 230V. Easy-to-maintain, seamLess-stainless steel interior chamber and epoxy powder-coated exterior are resistant to corrosion and chemical damage. Rugged, high-performance baths maintain water temperature from ambient to 99.9°C with  $\pm 0.2^\circ\text{C}$  uniformity (at  $37^\circ\text{C}$ ) and  $\pm 0.1^\circ\text{C}$  control resolution (at  $37^\circ\text{C}$ ) with stainless-steel gable cover. Front-mounted controls simplify operation. Overtemperature safety circuitry prevents thermal runaway. Allows temperature setpoint with  $\pm 0.1^\circ\text{C}$  Precision® at the push of a button. Microprocessor control with bright three-digit led temperature readout. Automatic overtemperature protection. Shipping weight: 16lbs. Model:282 Shallow Chamber. Chamber: Stainless Steel. Cabinet: Epoxy Powder-Coated Stainless Steel. Operating Temperature: 99.9°C. Capacity: 5.5L (1.5gal). Interior Dimensions (L x W x D): 11.5 x 6 x 6-Inch. Exterior Dimensions (L x W x H): 15.25 x 8 x 9.75in. Voltage rating: 230V. Frequency: 50/60Hz. Power rating: 300W.



Connect With Us

