

# Ultrasonic Cleaner Single Frequency Type



Feature ;

1. Digital display, easy operation for time and temperature setting.
2. count-down time and actual temperature real time displaying.
3. Temperature control range: 0 - 80°C.
4. Time setting range: 1-30 min.
5. Fully microprocessor controlled and programmable.
6. Very Reliable Industrial-Grade Transducer.
7. High capacity and quality stainless steel tank.
8. Stainless steel basket and lid.

| Model    | External Size L*W*H(mm) | Tank Size L*W*H (mm) | Capacity (L) | Ultrasonic Frequency (KHz) | Ultrasonic Power (W) | Heating Power (W) | Time Range(min) |
|----------|-------------------------|----------------------|--------------|----------------------------|----------------------|-------------------|-----------------|
| UC-08A   | 180*170*140             | 150*140*65           | 1.3          | 40                         | 60                   | 50                | 1-30            |
| UC-10A   | 180*170*180             | 150*140*100          | 2            |                            | 80                   | 50                |                 |
| UC-20A   | 270*170*210             | 240*135*100          | 3            |                            | 120                  | 100               |                 |
| UC-30A   | 330*180*270             | 300*150*150          | 6            |                            | 180                  | 200               |                 |
| UC-40A   | 330*270*270             | 300*240*150          | 10           |                            | 240                  | 250               |                 |
| UC-50A   | 330*270*320             | 300*240*200          | 14           |                            | 300                  | 400               |                 |
| UC-60A   | 360*330*270             | 330*300*150          | 15           |                            | 360                  | 400               |                 |
| UC-70A   | 360*330*320             | 330*300*200          | 19           |                            | 420                  | 600               |                 |
| UC-80A   | 550*330*270             | 500*300*150          | 22           |                            | 480                  | 600               |                 |
| UC-100A  | 550*330*320             | 500*300*200          | 30           |                            | 600                  | 800               |                 |
| UC-5S    | 208*192*210             | 150*140*100          | 2            | 80                         | 50                   | 200               | 1-480           |
| UC-10S   | 320*174*280             | 300*150*100          | 4            |                            | 100                  | 600               |                 |
| UC-20S   | 320*174*340             | 300*150*150          | 6            |                            | 200                  | 600               |                 |
| UC-20SII | 410*350*380             | 300*150*180          | 8            |                            | 200                  | 600               |                 |
| UC-30S   | 320*264*340             | 300*240*150          | 10           |                            | 300                  | 600               |                 |
| UC-30SII | 640*350*400             | 300*240*180          | 13           |                            | 300                  | 400               |                 |
| UC-50S   | 840*410*400             | 500*300*180          | 27           |                            | 500                  | 800               |                 |
| UC-60S   | 840*410*400             | 500*300*180          | 27           |                            | 500                  | 800               |                 |
| UC-70S   | 840*410*410             | 500*300*180          | 27           |                            | 500                  | 800               |                 |

